**Your Cart**

Total Items

Subtotal: \$

CHECK OUT
[Your Account](#) | [Cool Stuff](#) | [Customer Service](#) | [Tech](#) | [Products](#) | [Company Info](#)
Search:


By part number, OEM number, manufacturer, bike type or keyword.

SEARCH**Products:****Last Chance Sale!**

Antique
 Batteries
 Books
 Brakes
 Carburetors
 Dash/Speedo
 Driveline
 Electrical
 Engines
 Exhaust
 Fenders
 Footpegs/Floorboards
 Fork Assembly
 Forward Controls
 Frames
 Gas Tanks
 Gifts and Apparel
 Handlebar Controls
 Handlebars
 J&P Apparel
 License Plates, Horns and Hardware
 Lighting
 Lubricants
 Oil Tanks
 Saddlebags
 Seats
 Security, Lifts, Trailers, Covers
 Tires
 Tools
 Touring Accessories
 Transmissions
 Wheels
 Windshields & Mirrors

Rivera - Sometime's it's the Little Things that Count

Rivera Engineering and Primo Belt Drives regular customers have come to expect only the best, and we don't like to disappoint them. We are constantly upgrading and improving our extensive line of products and accessories to keep our customers satisfied.

Cover Up

use with any open belt drive system to protect the belt and belt pulleys from incidental damage caused by rocks and other flying road debris. Available immediately, this guard (part number PP-0671-P) is manufactured from aircraft quality billet aluminum and show polished ready to bolt on.

Our all new "Diamond" belt drive cover for the Brute IV belt drive imitates the early style outer primary cover that was original equipment on

Harley-Davidson® motorcycles from 1936 to 1965. A quality belt guard is always recommended for

Diaphragm Clutch Springs


for street performance and touring, and the gold spring is for competition.

All Primo Belt Drives systems as well as Rivera Engineering's Pro Clutch use our proprietary diaphragm clutch springs seen here. Available in three different strengths and colored for identification; the black spring is for street use on stock motorcycles, the silver spring is

The black spring is very light handed for high traffic and commuting. The silver is relatively easy on the hand, with faster action than the black spring, with significantly increased clutch pack pressure. It's very popular with the street performance crowd. The gold spring is recommended for competition use only and is our maximum effort spring. Drag racers win consistently with the heavy duty gold spring. These diaphragm springs can be quickly and conveniently swapped as needed.

Numbered Pulley

Tuning your Brute IV equipped Big Twin Harley-Davidson® just got easier. Primo Belt Drives offers the laser etched numbered 3" pulley seen at bottom left for spot-on tuning and timing procedures without removing the timing plug. It's easy to "degree" any Harley

**The latest fr (as of 4/15)**

- [Read](#)
- [Expre](#)
- [Becom](#)
- [Read](#)
- [Dictio](#)
- [Sturg](#)
- [Find u](#)
- [Triple](#)
- [Geom](#)
- [More](#)
- [Power](#)
- [Calcu](#)
- [Final](#)
- [more](#)

**BEST AVAILABLE COPY**




It's easy, to degree an angle, Big Twin motor with Primo's numbered 3" pulley and it adds a competition look to any motorcycle.

Choppers are back!



And more popular than ever! Everywhere you look you see rigid frame, chopper style machines reminiscent of the late 1960's and early 1970's. Stripped and clean, lean and mean, choppers were built rude to annoy the squares. Dual upswept exhaust systems were designed to vent spent exhaust gases and noise right at the window level of most automobiles to deafen the poor driver. Rivera Engineering's chopped muffler is not as loud as the originals with a permanent glass pack and a mellow low note, but its shape says chopper like nothing else. Awesome for dual upswept applications.

Offset for Fat Tires



Pay attention all you 1991-2002 Big Twin 5-speed owners:

You can now offset the transmission and primary allowing the use of a super-wide rear tire! This kit uses an extra length trans main shaft and sprocket shaft extension to move the primary drive components to the left either 12mm (approx. 0.5") or

25mm (approx. 1"). This, in turn, moves the drive belt to the left allowing for the use of a wider tire. Retaining the stock width rear belt the 12mm kit allows for the use of a 200 rear tire, the 25mm kit allows the use of a 230 tire (7.5" rim). If a chain final drive is used, up to a 250 tire (9" rim) can be utilized. Offset kits contain: primary space ring, crankshaft extender and nut, extra length transmission main shaft, extra length main drive 5th gear with needle bearing and seal, extra wide pulley spacer, extra length clutch push rod, extended jack shaft (25mm kit only), starter jack shaft spacer (12mm kit only), primary-to-tranny spacers, and all required mounting hardware. Wide swing arm and fender struts not included.

For more information on the above or other Primo Engineering products, call J&P Cycles® at 800-397-4844 in the USA and Canada. International customers call 319-462-4817. Or visit us on the web at www.jp-cycles.com.

BEST AVAILABLE COPY

US/Canada 24-Hour Customer Service Line: 800.338.1747
US/Canada 24-Hour Order Line: 800.397.4844
Worldwide Voice Line: 319.462.4817
Worldwide Fax: 319.462.4283

Copyright © 2002
J&P Cycles
All rights reserved.

J&P Cycles
13225 Circle Drive
PO Box 138
Anamosa, IA 52205

Web Site Support:
webmaster@jpcycles.com
Customer Service:
customerservice@jpcycles.com
Technical Support:
tech@jpcycles.com
International Customer Service:
internl@jpcycles.com